

# Floor and Wall Solutions

Order Samples at 331-702-2178 www.mondanicollection.com

## **Blend**

A beautiful union of cement and fabric create a unique tile with the warmth of textiles and the strength of concrete.

- 1. 6 Colors
- 2. Matte finish
- 3. 12" x 24"
- 4. Mosaics and trim available



## Sizes, Mosaics and Trims



12x24



2x2 Mosaics Sheet Size: 12x12



1x3 Interlocking Mosaics Sheet Size: 12x14



Bullnose 3x12





### Floor and Wall Solutions

Order Samples at 331-702-2178 www.mondanicollection.com

#### 1. FINISHES:

Matte

Thickness: 8 mm

Recommended Grout Joint: 3/32" or greater

All sizes modular with 3/16" grout joint

Grout joints of 1/8" inch or less, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

#### 2. TECHNICAL DATA

Physical Prop-	ASTM	Industry Stan-	Mondani
erties	Test	dards	Results
Water Absorption	C373	Impervious < 0.5%	Pass
		·	
Bond Strength	C482	≥ 50 psi	200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
	Scratch Test		
Hardness (Mohs)	(No regulated)	Range 0 - 10	6
Frost Resistance	(140 ICSUIDICA)	No sample must	Ĭ
(- (-)		show alterations to	_
(Freeze/Thaw)	C1026	surface No Requirement	<u>Pass</u>
Chemical Resis-			
tance	C650	Range E - A	Unaffected
	DCOF Acutest		
Coefficient of Fric-	DII .		
tion (Dynamic)	(wet)	≥ 0.42*	> 0.42
	Visual Evalua-	No Requirement	
Aesthetic Classifi-	tion Shade &		
cation	Texture	Range V0 – V4	V2

<sup>\*</sup>All values given are for matte and semi-polished. No values are given for polished material. Mondani Collection. does not recommend polished surfaces in area subject to exposure from grease, oil or water.

For level interior spaces to be walked upon when wet (see ANSI A137.1 section 6.2.2.1.10 – Section 9.6 for test procedure).


#### 3. INSTALLATION

All installation work using Mondani Collection tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

Installation or setting materials:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.







# Floor and Wall Solutions

Order Samples at 331-702-2178 www.mondanicollection.com





